

## Newlook Concrete Color Maintenance System



Materials: Pavemend 5.0™  
Pavemend SLQ™  
Pavemend 15.0™  
Pavemend VR™  
Pavemend TR™  
Surfix™

### 1.0 General Recommendations

- The following information should be considered and referenced when using these products.
- Read the instructions/label on Manufacturer's label and/or instructions guide.

### 2.0 Specific Recommendations

- All design elements (i.e., control joints, construction joints and expansion joints in pavements, sidewalks, curbs, concrete structures, etc.) present at the location of the repair must be reestablished.
- Adequate curing of the Pavemend materials must be achieved prior to application of the topical coloration. Typical time-frame is 24 hour cure minimum.
- The recommended procedure for application is described in the following steps:
  1. Remove all debris, coatings, paint, oils, etc.
  2. Pressure washing is required to ensure an open pore structure.
  3. Mix and apply topical coatings and stains as per Manufacturer's recommendation (See Appendix A & B)
  4. Cure all products accordingly
    - a. Do not wet area for a minimum of 24 hours
    - b. Foot traffic in 2 and 8 hours depending on ambient conditions.
    - c. Wheeled traffic in 48 hours (recommend protection from oils for up to 28 days)



For questions regarding product use and applications, contact our technical representatives at 1.888.341.2600 or visit [www.ceratechinc.com](http://www.ceratechinc.com)

CERATECH INC 1500 N. Beauregard St. Ste 320 Alexandria, VA 22311 800.581.8397

---

## Appendix A

---

### Solid Color Stain Kit

**Kit contents:**

4 Containers A-B-C-D  
Full Size kit = 32 oz bottles  
Small kit = 4 oz bottles

**Additional tools required:**

Applicator	Power Drill
Mixer	Water Source
Bristle brush	2 buckets; at least 3 gallons
Broom handle	

---

### Mixing

- Pour containers A and B into 1st bucket and mix well
- Pour containers C and D into 2nd bucket
- Completely re-fill container C with water and shake, pour into 2nd bucket
- Repeat a Total of 4 times
- Mix well
- Pour 1st bucket into 2nd bucket
- Mix several minutes with paddle and drill
- Stir bottom of bucket with brush to ensure complete mixing

---

### Application

- Dip applicator into bucket and saturate in a circular motion. Be sure to do this EVERY time.
- Spread stain onto application area. DO NOT apply pressure.
- Spread stain evenly across application area in circular motions until it does not puddle.
- Broom in multiple directions for even coverage.

---

## Appendix B

---

### Color Enhancer Kit

**Kit contents:**

3 Containers A-B-C

**Additional tools required:**

Applicator or garden sprayers	Power Drill
Mixer	Water Source
Bristle brush	1-gallon bucket or larger
Broom handle	

---

### Mixing

- Pour containers A and B into bucket and mix well
- Pour container C into bucket
- Completely re-fill container C with water and shake, pour into bucket
- Repeat a Total of 3 times
- Mix well

---

### Application

- Spread enhancer evenly across application area with sprayer or broom in circular motions.
- Repeat application until desired coloration is achieved.



For questions regarding product use and applications, contact our technical representatives at 1.888.341.2600 or visit [www.ceratechinc.com](http://www.ceratechinc.com)

CERATECH INC 1500 N. Beaugard St. Ste 320 Alexandria, VA 22311 800.581.8397